



AVECS™
PRO-CURE DATA SHEET
AVECS.BUILD 1-800-VECS-658

PRODUCT DESCRIPTION:

PRIMARY USE OF **AVECS PRO-CURE** IS A WATER BASED SPRAY ON LIQUID DESIGNED TO PENETRATE GREEN CONCRETE THE DAY IT IS POURED TO ELIMINATE THE NEED TO WET CURE SLABS PER ACI RECOMMENDATIONS AND DOES NOT REQUIRE REMOVAL AS DO CURING COMPOUNDS MOST OF WHICH ARE PARRAFIN OR PETROLEUM BASED AND CAN INHIBIT BOND. **PRO-CURE** ALSO HELPS RESIST PENETRATION OF ACIDS, OILS, GRAFFITI, ETC. GREAT FOR CONCRETE SLABS ON-GRADE, BELOW-GRADE, ELEVATED DECKS AND CERTAIN ROOF APPLICATIONS WHICH WOULD NORMALLY TURN INTO VAPOR AND POTENTIALLY CAUSE DELAMINATION OF FINISHES. **AVECS PRO-CURE** GIVES YOU ACCESS TO ALL TRADES (EXCEPT FLOORING INSTALLATION) ON THAT SLAB THE VERY NEXT DAY THUS ACCELERATING YOUR SCHEDULE. **AVECS PRO-CURE** SHOULD BE USED SOLELY AS THE METHOD OF CURING THE SLAB AND NOT WITH OTHER CURING AGENTS.

CAUTIONS & LIMITATIONS:

DO NOT SPRAY **AVECS PRO-CURE** ON A SLAB WHEN AMBIENT TEMPERATURE IS LESS THAN FORTY (40) DEGREES. SURFACE SHOULD BE PREPARED ACCORDING TO INDUSTRY GUIDELINES BEFORE APPLICATION AND NO FREE STANDING WATER SHOULD EXIST AT TIME OF APPLICATION.

OTHER SIDE BENEFITS:

- SUBSTANTIALLY REDUCES SLAB CURL AND DOES WHAT WET CURING DOES BUT WITHOUT NEED TO REMOVE OR RESTRICT ACCESS FOR 3-7 DAYS LIKE WET CURING (ASTM C-309/ PART 6 COMPLIANT FOR WATER RETENTION)
- ELIMINATES SURFACE DUSTING
- ESCALATES SCHEDULE AS THERE IS NO DOWN TIME WHILE WET CURING AND NOTHING TO REMOVE BEFORE FLOORING INSTALLATION
- GREATLY REDUCES SHRINKAGE/SURFACE CRACKS AND SPAWLING
- INHIBITS ACIDS, AND CHEMICAL ATTACK/INTRUSION

TECHNICAL DATA:

ENVIRONMENTAL- **AVECS CURE** IS 100% VOC FREE AND POSES ZERO THREAT TO THE ENVIRONMENT.
PHYSICAL & CHEMICAL PROPERTIES- TEST REPORTS AVAILABLE TO INDUSTRY PROFESSIONALS

APPLICATION:

HANDLE AND STORE PRODUCT ACCORDING TO **AVECS** RECOMMENDATIONS. AT POINT WHEN CONCRETE CAN BE WALKED ON WITHOUT MARRING THE SURFACE YOU ARE READY TO APPLY **AVECS PRO-CURE**. PRE-MIXED SO IT IS READY TO DISPENSE. FILL HUDSON, OR LIKE, SPRAYER AND APPLY GENEROUSLY UNTIL A SHEEN IS VISIBLE. OVERLAP EACH ROW TO ENSURE THOROUGH COVERAGE. AS PROGRESS IS MADE MAKE SURE THAT MATERIAL DOES NOT PUDDLE. IF IT DOES, USE A CLEAN BRISTLE BROOM AND DISPERSE EXCESS **AVECS PRO-CURE**. FOLLOW **AVECS** INSTRUCTIONS FOR DISPENSING. WHEN SLAB DRIES COMPLETELY YOU CAN ACCESS FLOOR IMMEDIATELY.

SPREAD RATE: 250-300SF PER GALLON AND SOLD IN 5 GALLON PAILS. (55 GALLON DRUMS AVAILABLE VIA SPECIAL REQUEST)

PRECAUTIONS: AN **AVECS** APPROVED REPRESENTATIVE MUST BE PRESENT FOR FIRST APPLICATION UNLESS PRE-AUTHORIZED TO PROCEED WITHOUT.

STORAGE: STORE **AVECS PRO-CURE** ABOVE 45 DEGREES AND DO NOT ALLOW IT TO FREEZE. PRODUCT SEPERATION MAY OCCUR, REQUIRING AGITATION.

WARRANTY:

THE **AVECS PRO-CURE** WAS DEVELOPED PRIMARILY FOR INTERIOR SLABS TO ELIMINATE NEED FOR WET CURING SLABS AND TO ELIMINATE REMOVAL ISSUES OF COMPOUNDS AND EXCEEDS ALL GUIDELINES PERTAINING TO MOISTURE RELATED FAILURES ESTABLISHED BY FLOORING MANUFACTURERS. **PRO-CURE** IS WARRANTED AGAINST DEFECTS FROM OUR MANUFACTURING FACILITY BUT IS NOT WARRANTED AS A SOLUTION TO ADDRESS MVE BY ITSELF.

COMPATIBILITY:

AVECS PRO-CURE ENHANCES BOND OF FLOORING AND PRODUCT IS COMPATIBLE WITH ALL FLOORCOVERING, ADHESIVE, PATCHING COMPOUND AND SELF-LEVELER.

TECHNICAL SERVICE/INFO: FOR EMAIL INFORMATION CONTACT INFO@AVECS.BUILD OR PLEASE CALL 1-800-VECS-658.